

Single Mode Standard Tree Coupler Module SMTC-MxN (M: 1 or 2)

Features

Wide Bandwidth and Low Insertion
Low Insertion Loss
High Quality and Reliability

Applications

Fiber Distribution Network
CATV Network
Test Equipment

Specifications

Parameters	Unit	Values			
Configuration		1 or 2 × 4	1 or 2 × 8	1 or 2 × 16	1 or 2 × 32
Center Wavelength	nm	1310 or 1550			
Operating Wavelength Range	nm	±20			
Max. Insertion Loss	dB	6.7	10.0	13.3	16.6
Max. PDL	dB	0.2	0.3	0.4	0.5
Max. Uniformity	dB	0.8	1.2	1.8	2.4
Min. Directivity	dB	50			
Package Dimensions		106mmX79mmX10mm (for 1, 2X4)			
		125mmX96mmX15mm (for 1, 2X8)			
		145mmX116mmX18mm (for 1, 2X16, 1, 2X32)			
		LGX Compatible			
Max. Optical Power (CW)	mW	500			
Max. Tensile Load	N	5			
Fiber Type		SMF-28e Fiber			
Operating Temperature	°C	-5 to +70			
Storage Temperature	°C	-40 to +85			

*Above specifications are for module without connector.

*For module with connectors, IL will be 0.3dB higher and RL will be 5dB lower.

Ordering information

ASMTC-①①-②②②②-③③-④④-⑤⑤-⑥-⑦

①①: Wavelength

31 - 1310nm

55 - 1550nm

SS - Specify

③③: Coupling Ratio

01 - 01/99

05 - 05/95

10 - 10/90

50 - 50/50

SS - Specify

⑤⑤: Fiber Jacket on Port 1 & 2

L - 900um Loose Tube

C - 3mm Loose Cable

S - Specify

②②②②: Port

0104 - 1×4

0108 - 1×8

0116 - 1×16

0132 - 1×32

0204 - 2×4

0208 - 2×8

0216 - 2×16

0232 - 2×32

④④: Connector Type on Port 1 & 2

1 - FC/UPC

2 - FC/APC

3 - SC/UPC

4 - SC/APC

N - None

S - Specify

⑥: Fiber Length

0.5 - 0.5m

S - Specify

⑦: Package Dimensions

A - 106mm×79mm×10mm (for 1,2x4)

B - 125mm×96mm×15mm (for 1,2X8)

C - 145mm×116mm×18mm (for 1,2x16,1,2x32)

D - LGX compatible

S - Specify